



Premium Synthetic Blend

- 1.5x longer lasting than conventional motor oil
- More cleaning power to maximize engine efficiency & fuel economy
- 15x more resistance to viscosity breakdown

Full Synthetic

- 30% better wear protection in high / low temps*
- 40% cleaner engine which maximizes your fuel economy*
- 2x longer life than conventional motor oil*

Full Synthetic Euro

- Engineered to surpass vigorous tests of European OEM's
- First-rate performance and protection in extreme temps
- Perfect balance between powerful detergents & anti-wear additives



* Compared to ILSAC and API industry standards

LUBRICANTS



LUBRICANTS

PCMO Data



GulfTEC® SYNTHETIC MOTOR OIL

Full synthetic formulation specially designed to provide enhanced engine protection against heat, deposits and wear.

SAE Viscosity Grade	0W-16	0W-20	0W-30	0W-40	5W-20	5W-30	10W-30
Product Code	330208	330212	330215	330218	330210	330211	330213
Viscosity, cSt @ 40°C	36.5	46.0	60.5	73.6	45.8	61.5	65.5
Viscosity, cSt @ 100°C	7.2	8.6	10.8	13.2	8.5	11.0	10.4
Viscosity Index	162	168	175	181	165	175	147
Cold Cranking at temp °C, cP	5000 @ -35	5000 @ -35	5500 @ -35	5700 @ -35	5200 @ -30	5000 @ -30	4800 @ -25
Highest API / ILSAC Performance	SP/GF-6B	SP/GF-6A	SP/GF-6A	SP	SP/GF-6A	SP/GF-6A	SP/GF-6A

GulfTEC® dexos1™ Gen 3 SYNTHETIC MOTOR OIL

Licensed to the latest General Motors dexos1™ Gen 3 Oil Spec. - GM certified for factory and service fill – backwards compatible for all older GM vehicles.

SAE Viscosity Grade	0W-20	5W-20	5W-30
Product Code	330226	330227	330228
Viscosity, cSt @ 40°C	44.0	45.8	62.6
Viscosity, cSt @ 100°C	8.2	8.3	11.1
Viscosity Index	163	159	171
Pour Point, °C	-42	-39	-40
Highest API/ILSAC Performance	SP/GF-6A	SP/GF-6A	SP/GF-6A

GulfTEC® REVOLUTION EURO SYNTHETIC MOTOR OIL

Recommended for European four-stroke gas and light duty diesel engines in passenger cars, sport utility vehicles, and light duty trucks

SAE Viscosity Grade	5W-30	0W-30	5W-40
Product Code	330350	330352	330354
Viscosity, cSt @ 40°C	68.5	63.5	81.0
Viscosity, cSt @ 100°C	11.8	12.0	14.0
Viscosity Index	173	190	180
Cold Cranking at temp °C, cP	5500 @ -30°C	6200 @ -35°C	6000 @ -30°C
High-Temp/High-Shear Viscosity, cP @ 150°C	3.6	3.6	3.8

GULFPRIDE® PREMIUM MOTOR OIL

Premium quality synthetic blend motor oil exceeds the latest manufactures performance requirements for wear protection and improved fuel economy

SAE Viscosity Grade	5W-20	5W-30	10W-30
Product Code	330132	330133	330136
Viscosity, cSt @ 40°C	46.0	60.5	75.0
Viscosity, cSt @ 100°C	8.3	10.5	11.5
Viscosity Index	155	160	142
Cold Cranking at temp °C, cP	5500 @ -30	5800 @ -30	5200 @ -25
Highest API / ILSAC Service	SP / GF-6A	SP / GF-6A	SP / GF-6A

GULFTEC FULL SYNTHETIC HIGH MILEAGE MOTOR OIL

Formulated to improve the life of older, high mileage vehicles with added engine protection and enhanced seal conditioning

SAE Viscosity Grade	0W-20	5W-20	5W-30	10W-30
Product Code	330360	330362	330364	330366
Viscosity, cSt @ 40°C	44.5	52.0	62.0	68.0
Viscosity, cSt @ 100°	8.4	8.8	10.5	10.6
Viscosity Index	171	153	158	143
Cold Cranking at temp °C, cP	5200 @ -35	5400 @ -30	4800 @ -30	5500 @ -25
Highest API / ILSAC Service	SP/GF-6A	SP/GF-6A	SP/GF-6A	SP/GF-6A

GULFPRIDE® MOTOR OIL

Outstanding engine protection for hardworking gasoline engines often subject to severe service when hauling and towing heavy loads at sustained speeds

SAE Viscosity Grade	10W-40	20W-50	30	40
Product Code	330135	330137	330163	330164
Viscosity, cSt @ 40°C	112.0	155.0	89.5	130.0
Viscosity, cSt @ 100°C	15.5	18.7	11.1	14.3
Viscosity Index	146	136	110	109
Pour Point °F	-33	-22	-11	-7
Highest API Service	SP	SP	SP	SP