



LUBRICANTS

Product Data Sheet

GulfTEC® Full Synthetic 0W-8

Advanced Hybrid Motor Oil – JASO GLV-1 Protection

GulfTEC® Full Synthetic 0W-8 Motor Oil is a premium, low-viscosity engine oil developed specifically for Asian and North American hybrid and gasoline vehicles that require a SAE 0W-8 viscosity grade. Engineered with premium synthetic base stocks and the latest additive technology, it offers enhanced fuel economy, exceptional engine protection, thermal stability as well as helping to prevent engine deposits and sludge buildup. **GulfTEC® Full Synthetic 0W-8 Motor Oil** meets the stringent requirements of **JASO GLV-1**.

Features and Benefits

- Enhanced Fuel Economy
- Excellent Low Temperature Performance
- Superior Wear Protection
- Outstanding Oxidation Control
- Exceptional Shear Stability
- Outstanding Deposit and Sludge Control
- Outstanding Engine Protection

Typical Properties

SAE Grade	Test Method	0W-8
Product Code		330206
Meets Requirements Set By:		JASO M364 GLV-1
Kinematic Viscosity, cSt at 40°C	ASTM D-445	28.7
Kinematic Viscosity, cSt at 100°C	ASTM D-445	5.7
Viscosity Index, calculated		144
Flash Point, °C	ASTM D-92	222
Pour Point, °F (°C)	ASTM D-97	-58 (-50)
Cold Cranking at temp °C, cP	ASTM D-5293	4800 at -35°C
Specific Gravity, 60°F	ASTM D-1298	08458
Density, lb/gal		7.05

Note: Typical values shown are representative of current production and may vary within modest range.

Rev 7/24



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

