



LUBRICANTS



Product Data Sheet

Anti-Chatter Axle Additive

Reduces noise, vibration, and premature gear wear

Specially formulated friction-modified gear oil additive used to help eliminate the stick-slip chatter often found in heavily loaded differentials and wet brake systems in heavy duty off-road construction equipment. Extreme pressure (EP) additives help to prevent damage to the gears and allows the gear oil to perform over a wide range of temperature, load, and speed.

Features and Benefits

- Non-foaming-rapid air release
- Surpasses API GL-4 gear oil performance
- Maintains viscosity under severe service conditions
- Friction modifiers for superior wet brake chatter control
- Outstanding wear protection for heavily loaded gears in off-road equipment

Applications

- Recommended treat rate - Approximately 6 to 10% of total axle oil volume

Typical Properties

	Test Method	
Product Code		330100
Viscosity, cSt @ 100°C	ASTM D-445	23.5
Viscosity Index	ASTM D-2270	108
Pour Point, °C	ASTM D-5949	-16°C
Flash Point, COC, °C	ASTM D-92	215°C
Specific Gravity	ASTM D-4052	1.033

Note: Refer to equipment owner's manual for proper lubricant recommendation



1-800-566-4853



East Greenbush, NY



www.nu-tierbrands.com

